

A detailed schematic diagram of a mechanical assembly, likely a pump or engine component, enclosed in a rectangular frame. The diagram includes several circular and cylindrical parts, each with internal features and labels. Key components and labels include:

- Central Assembly:** A large central circle labeled **1** with a central point **1A**. To its right is a smaller circle labeled **3** with a central point **3A**. Below these are two more circles, **5** and **7**, with internal dashed lines and labels **5A** and **7A** respectively. A small circle **6** is located between circles **1** and **3**.
- External Components:**
 - Top left: A vertical assembly labeled **9** with a circular component **21** and a label **V1** with an arrow pointing right.
 - Top right: A vertical assembly labeled **15** with a label **Npp** and a label **Nn** with a plus sign and an arrow pointing right.
 - Bottom right: A vertical assembly labeled **11** with a label **P2** and a label **V3** with an arrow pointing right.
 - Bottom left: A circular component labeled **17** with a label **P2** and a label **20** with a plus sign and an arrow pointing right.
- Internal Labels and Features:**
 - 13**: A label near the top right, pointing to a curved surface.
 - 14**: A label near the top center, pointing to a vertical component.
 - 16**: A label near the bottom center, pointing to a circular component.
 - 18**: A label near the bottom right, pointing to a circular component.
 - 19**: A label near the bottom center, pointing to a circular component.
 - 23**: A label near the bottom center, pointing to a circular component.
 - P1**, **P2**, **P3**: Labels pointing to various circular components.
 - f1**, **f3**: Labels pointing to specific points or features on the central circles.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

"Device for embossing and laminating web material consisting of two or more plies"

Description

Technical Field

5 The present invention relates to a device for embossing and laminating continuous plies in order to form a web material.

 More specifically, the present invention relates to an embossing and laminating device of the type comprising a pair of embossing cylinders, each of which works in conjunction with a corresponding pressure roller, with
10 a glue applicator which applies glue to at least one of the embossed plies, and with laminating means which join together two plies that have been embossed separately between each embossing cylinder and its corresponding pressure roller.

Background Art

15 In the paper-converting industry, embossing is often used in the production of toilet paper, kitchen towels, paper serviettes, tissues and similar products in order to modify the paper's softness and absorbency.

 There are various embossing and laminating systems for the production of embossed web materials obtained by joining together two or
20 more plies. In particular, systems exist in which two or more plies of continuous material are embossed separately and then joined together. These systems can basically be subdivided into tip-to-tip laminating systems and nested laminating systems, so-called random nested or "DERL" systems or the like.

25 In the first case (see EP-B-0,370,972), each of the two plies is embossed between an embossing cylinder, which has projections or tips arranged in a repeating pattern, and a pressure roller, which is usually covered in a yielding material such as rubber or the like. The two plies are then joined together by being laminated between the two opposing embossing
30 cylinders which are synchronized so that the tips of one cylinder coincide with the tips of the other cylinder in the lamination nip between the two cylinders, the distance between the cylinders being such as to cause lamination of the plies between the opposing tips. A glue is usually applied to one of the two plies - to the raised areas produced by the embossing action - prior to
35 lamination.

 With embossing and lamination of the "nested" type, on the other hand, the plies - which have been embossed separately in a way similar to that described above - are joined together so that the protrusions of one ply fit

between the protrusions of the other ply. In these cases the two embossing cylinders are not pressed against each other in the nip between them and the two plies are joined together by being laminated between one of the two embossing cylinders and a laminating roller. This technique is described in
5 GB-B-1,225,440 and in US-A-3,694,300.

Italian patent No. 1,213,842 (appl. No. 9519A/87) describes an embossing unit of the tip-to-tip type which has been modified in order to produce a random type nested embossed pattern ("DERL"). This is achieved by inserting a diverting element which modifies the path of one of the two
10 plies between the embossing zone and the lamination zone.

Italian utility model application No. 21,325B/89 describes a device that allows both nested type embossing and tip-to-tip type embossing to be carried out by modifying the position of the device members as and when necessary. Basically, in order to switch from one operational mode to the
15 other, the position of the embossing cylinders needs to be altered completely. In practice, what this known technique is in fact suggesting is to convert a conventional tip-to-tip embossing unit into a conventional nested embossing unit each time. This means that very lengthy intervention times are needed in order to change over from one type of embossing to the other. Furthermore,
20 in order to be able to position the laminating roller in this device such that it can work in conjunction with one of the embossing cylinders, it has been necessary to locate the axes of the two embossing cylinders and of the two pressure rollers in one and the same horizontal plane. This brings with it substantial drawbacks on account of the deformations experienced by the
25 embossing cylinders as a result of the high pressures required during embossing, with the effect that there is uneven embossing and lamination between the center and the edges of the plies.

Objects and Summary of the Invention

The object of the present invention is to produce an embossing
30 and laminating unit that can operate in both tip-to-tip and nested mode and in which it is easy to switch from one type of embossing to the other, with any operations to set and adjust the device being reduced a minimum.

A further object of the present invention is to produce an embossing unit in which the embossing cylinders and the pressure rollers are
35 positioned so as to reduce any irregularities in the laminated product which occur as a result of bending of the embossing cylinders.

These objects, together with other objects and advantages which will be apparent to those skilled in the art on reading the following text, are

achieved using an embossing and laminating device of the type comprising: a pair of embossing cylinders having tips arranged on the two rollers, said two embossing cylinders being positioned with their axes parallel and adjacent to each other so as to form a nip between them; a pair of pressure rollers, each of which works in conjunction with one of the embossing cylinders; a glue applicator associated with one of said embossing cylinders; and a laminating roller positioned downstream of the nip between the embossing cylinders and working in conjunction with the embossing cylinder which is associated with said glue applicator. Essentially, according to the invention, the embossing cylinder associated with the laminating roller has a diameter greater than that of the other embossing cylinder, and said two embossing cylinders have the same peripheral speed and can be synchronized so that the tips of one embossing cylinder coincide with the tips of the other embossing cylinder, or, alternatively, the tips of one embossing cylinder fit between the tips of the other embossing cylinder, without changing the distance between the centers of the cylinders. By using two cylinders having different diameters, sufficient space is created to insert a laminating roller downstream of the nip between the embossing cylinders, even when the two pressure rollers are positioned vertically, one above and one below the corresponding embossing cylinders, the axes of which lie in a horizontal plane.

If the space created by using one embossing cylinder with a diameter greater than that of the other is not sufficient to position the laminating roller, provision may advantageously be made to further increase the space available by ensuring that the plane containing the axes of the embossing cylinder with the larger diameter and the corresponding pressure roller is not perpendicular to the plane containing the axes of the two embossing cylinders. This allows one of the two pressure rollers to be distanced from the plane which is tangential to the embossing cylinders and which passes through the nip between them and also makes more space available in which to position the laminating roller, as well as means for cleaning the surface of the cylinder with the larger diameter, said cleaning means being positioned along the periphery of the cylinder, between the laminating roller and the pressure roller. The cleaning means are used to remove glue residues and dust from the embossing cylinder which is associated with the glue applicator.

The angle formed by the two planes can typically be between 90 and 125° and preferably between 90 and 105°.

Brief Description of the Drawings

A better understanding of the invention will be gained by following the description and the appended drawing which shows a practical embodiment of said invention. More specifically, in the drawing:

Fig. 1 shows a diagram of the device according to the invention;

5 Fig. 2 shows an enlarged diagrammatic section of the nip between the two embossing cylinders during tip-to-tip operation;

Fig. 3 shows an enlarged diagrammatic section of the nip between the two embossing cylinders during nested operation; and

10 Fig. 4 shows an enlarged diagrammatic section of the lamination zone during nested operation.

Detailed Description of the Preferred Embodiment

Referring initially to Fig. 1, the device comprises a pair of embossing cylinders 1, 3, each of which has a plurality of tips or projections (shown diagrammatically in the subsequent Figs 2 to 4) arranged in geometric patterns symmetrically on the two cylinders. The diameter of the cylinder 1 is greater than that of the cylinder 3. The difference in diameter is about 30% in the example illustrated. The two cylinders 1, 3 are connected together mechanically so that they rotate in opposite directions, as shown by the arrows f1 and f3, and at the same peripheral speed. This can be achieved by an appropriate choice of transmission gears (not illustrated).

20 In a manner known per se, the embossing cylinder 1 works in conjunction with a pressure roller 5, while the cylinder 3 works in conjunction with a pressure roller 7. The two pressure rollers 5 and 7 are covered with a layer of elastically yielding material, for example rubber. Each pressure roller 5, 7 is pressed against its respective embossing cylinder 1, 3 by an actuator 9, 11.

30 The plane P1 containing the axes 7A, 3A of the pressure roller 7 and of the embossing cylinder 3 forms a 90° angle with the plane P2 containing the axes 1A and 3A of the two embossing cylinders 1, 3. In contrast, the plane P3 containing the axes 5A, 1A of the pressure roller 5 and of the embossing roller 1 forms an angle other than 90° with the plane P2. The obtuse angle formed between the two planes P2 and P3 is about 95-120°. It is kept at the minimum value compatible with the sizes of the parts in order to reduce the horizontal component of the deformation due to the pressure exerted by the pressure roller 5 on the embossing cylinder 1.

35 This set-up makes space available around the cylinder 1, between the roller 5 and the cylinder 3, in which to locate a laminating roller 13, which works in conjunction with the cylinder 1, for purposes which will be clarified

later, as well as a device 14 (of a type known per se) for cleaning the surface of the embossing cylinder 1. The laminating roller 13 is controlled by an actuator 15 so that it assumes an active position, indicated by solid lines in Fig. 1, in which it is pressed against the surface of the embossing cylinder 1, or an inactive position, indicated by dashed lines, in which it is not in contact with the cylinder 1.

A glue applicator 17, of a type known per se, is associated with the embossing cylinder 1. In the example illustrated it comprises two cylinders whose axes of rotation are coplanar with the axes 1A, 3A of the two embossing cylinders 1, 3 in order to reduce the effects of bending on the distribution of the glue and thus ensure that the glue is distributed evenly.

Two plies of material to be embossed, denoted V1 and V3, are fed to the device described hitherto. The reference 20 denotes a roller for guiding the ply V3 while the numerals 21 and 23 denote two widening rollers for the plies V1 and V3 respectively. The ply V1 is embossed between the embossing cylinder 1 and the pressure roller 5, while the ply V3 is embossed between the embossing cylinder 3 and the pressure roller 7. After embossing, a glue C is applied to the ply V1 by means of the applicator 17, in a manner known per se.

The two plies V1, V3 can at this point be joined together in two different ways, depending on how the two embossing rollers 1, 3 are synchronized in relation to each other and on the path followed by the plies downstream of the nip G between the embossing cylinders 1, 3.

Fig. 2 shows an enlargement of the nip G between the two embossing cylinders 1, 3 in the position assumed by them when the device is set for tip-to-tip embossing. In this case the two cylinders 1, 3 are synchronized so that the tips or projections 1P of the cylinder 1 are in phase with the tips or projections 3P of the cylinder 3, in other words so that, where the two cylinders 1, 3 are at their closest, the tips or projections of one cylinder press against the tips or projections of the other, laminating the two embossed plies V1 and V3 between them. The glue applied to the ply V1 causes the plies to stick together. Downstream of the nip G, the web material formed by the two joined plies V1 and V3 follows the path denoted Npp. With this set-up the laminating roller 13 is held away from the embossing cylinder 1.

Figs 3 and 4 show the positions of the embossing cylinders 1, 3 and of the laminating roller 13 when a nested embossed pattern is being produced. The centers of the two embossing cylinders 1 and 3 are set the

- 6 -

same distance apart as in the previous case, but they are synchronized differently so that the tips 1P of the embossing cylinder 1 fit between the tips 3P of the embossing cylinder 3. The two embossed plies V1 and V3 are no longer laminated in the nip G between the two embossing cylinders 1, 3 but rather downstream of the nip G, between the laminating roller 13 (which in this case is pressed against the tips 1P of the cylinder 1) and the embossing cylinder 1, as illustrated in the diagrammatic enlargement of Fig. 4. Downstream of the laminating roller 13 the web material produced by joining together the plies V1 and V3 follows the path Nn.

It should be understood that the drawing shows only one example, given solely as a practical demonstration, of the invention and that the forms and arrangements of the latter can vary without thereby departing from the scope of the underlying concept of said invention. The presence of reference numerals in the appended claims has the purpose of facilitating the reading of the claims with reference to the description and drawing and does not restrict the scope of protection represented by the claims.

Claims

1. Embossing and laminating device comprising: a pair of embossing cylinders (1, 3) having tips (1P, 3P) arranged on the two rollers, said two embossing cylinders being positioned with their axes parallel and adjacent to each other so as to form a nip (G) between them and rotating at the same peripheral speed and in opposite directions; a pair of pressure rollers (5, 7), each of which works in conjunction with one of the embossing cylinders; a glue applicator (17) associated with one of said two embossing cylinders; and a laminating roller (13) positioned downstream of the nip (G) between the embossing cylinders (1, 3) and working in conjunction with the embossing cylinder (1) which is associated with said glue applicator (17); characterized in that
- the embossing cylinder (1) associated with said laminating roller (13) has a diameter greater than that of the other embossing cylinder (3);
 - and the two embossing cylinders (1, 3) can be synchronized so that the tips (1P) of one embossing cylinder (1) coincide with the tips (3P) of the other embossing cylinder (3) or, alternatively, the tips (1P) of one embossing cylinder (1) fit between the tips (3P) of the other embossing cylinder (3).
2. Device according to Claim 1, characterized in that the two embossing cylinders can be synchronized essentially without changing the distance between the centers of the cylinders.
3. Device according to Claim 1 or 2, characterized in that said laminating roller (13) can either be made to press against the corresponding embossing cylinder (1) or be moved away from it.
4. Device according to Claim 1 or 2 or 3, characterized in that the plane (P3) containing the axes (1A, 5A) of the embossing cylinder (1) which is associated with said laminating roller (13) and of the corresponding pressure roller (5) forms an angle other than 90° with respect to the plane (P2) containing the axes (1A, 3A) of the embossing cylinders, and in that the plane (P1) containing the axes (3A, 7A) of the other embossing cylinder (3) and of the corresponding pressure roller (7) is essentially perpendicular to the plane (P2) containing the axes (1A, 3A) of the two embossing cylinders (1, 3).
5. Device according to Claim 4, characterized in that the axes (1A, 3A) of the two embossing cylinders (1, 3) lie in a horizontal plane.
6. Device according to one or more of the preceding claims, characterized in that the two pressure rollers (5, 7) are positioned one above and one below their respective embossing cylinders (1, 3) and in that the

embossing cylinder with the smaller diameter (3) is the one whose pressure roller (7) is positioned below it.

7. Device according to one or more of the preceding claims, characterized in that the embossing cylinder with the larger diameter (1) is associated with a cleaning device (14), the latter being positioned between the laminating roller (13) and the corresponding pressure roller (5).

8. Device according to one or more of the preceding claims, characterized in that the plane (P3) containing the axes (1A, 5A) of the embossing cylinder (1) with the larger diameter and of the corresponding pressure roller forms an angle of between 90 and 125°, and preferably of between 90 and 105°, with the plane containing the axes (1A, 3A) of the two embossing cylinders (1, 3).


9. Device according to one or more of the preceding claims, characterized in that said glue applicator (17) has one or more glue transfer or application cylinders, whose axes of rotation are coplanar with the axes of the two embossing cylinders.

10. Embossing and laminating device comprising: a pair of embossing cylinders (1, 3) having tips (1P, 3P) arranged on the two rollers, said two embossing cylinders being positioned with their axes parallel and adjacent to each other so as to form a nip (G) between them and rotating at the same peripheral speed and in opposite directions; a pair of pressure rollers (5, 7), each of which works in conjunction with one of the embossing cylinders; a glue applicator (17) associated with one of said two embossing cylinders; and a laminating roller (13) positioned downstream of the nip (G) between the embossing cylinders (1, 3) and working in conjunction with the embossing cylinder (1) which is associated with said glue applicator (17); characterized in that

a plane (P3) containing the axes (1A, 5A) of the embossing cylinder (1) which is associated with said laminating roller (13) and of the corresponding pressure roller (5) forms an angle other than 90° with respect to a plane (P2) containing the axes (1A, 3A) of the embossing cylinders, and in that a plane (P1) containing the axes (3A, 7A) of the other embossing cylinder (3) and of the corresponding pressure roller (7) is essentially perpendicular to the plane (P2) containing the axes (1A, 3A) of the two embossing cylinders (1, 3).



1/3

FIG. 1



THIS PAGE BLANK (USPTO)


2/3



THIS PAGE BLANK (USPTO)

3/3

FIG. 4



THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IT 98/00134

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 B31F1/07		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 6 B31F		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X, P	WO 97 20689 A (PERINI FABIO SPA ;BIAGIOTTI GUGLIELMO (IT)) 12 June 1997 see abstract; figure 1	1, 6, 9, 10
X	IT 1 213 842 B (PERINI FINANZIARIA) 5 January 1990 cited in the application see figures	1, 10
A	EP 0 265 298 A (BEGHIN SAY SA) 27 April 1988 see figures	1, 10
A	FR 2 684 598 A (KAYSERSBERG SA) 11 June 1993 see figures	1, 3
-/-		
<div style="display: flex; justify-content: space-between;"> <input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex. </div>		
<div style="display: flex;"> <div style="flex: 1;"> <p>* Special categories of cited documents :</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="flex: 1;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p> </div> </div>		
Date of the actual completion of the international search		Date of mailing of the international search report
17 September 1998		10/11/1998
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Kosicki, T

INTERNATIONAL SEARCH REPORT

International Application No
PCI/IT 98/00134

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 370 972 A (PERINI FINANZIARIA SPA) 30 May 1990 cited in the application see figures -----	1,10
A	US 3 694 300 A (SMALL RUDOLPH ERNST) 26 September 1972 cited in the application see figures -----	1,10
A	IT 2 132 589 U (ALBERTO CONSANI S.P.A.) 27 March 1991 cited in the application see figures -----	1,10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IT 98/00134

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9720689	A	12-06-1997	IT FI950248 A AU 1108597 A	05-06-1997 27-06-1997
IT 1213842	B	05-01-1990	NONE	
EP 0265298	A	27-04-1988	FR 2604734 A CA 1299079 A US 4978565 A	08-04-1988 21-04-1992 18-12-1990
FR 2684598	A	11-06-1993	AT 127732 T DE 69204825 D DE 69204825 T EP 0570578 A FI 933497 A WO 9311929 A	15-09-1995 19-10-1995 04-04-1996 24-11-1993 06-08-1993 24-06-1993
EP 0370972	A	30-05-1990	CA 2003276 A,C ES 2036055 T GR 3006871 T JP 1892587 C JP 2182444 A JP 6013198 B KR 9410352 B US 5096527 A	23-05-1990 16-04-1998 30-06-1993 26-12-1994 17-07-1990 23-02-1994 22-10-1994 17-03-1992
US 3694300	A	26-09-1972	BE 787144 A CA 970672 A DE 2236445 A FR 2151939 A GB 1378057 A JP 48033161 A SE 373171 B	01-12-1972 08-07-1975 08-03-1973 20-04-1973 18-12-1974 08-05-1973 27-01-1975
IT 2132589	U		NONE	

THIS PAGE BLANK (USPTO)